




RoHS Compliant

REV	DESCRIPTION OF CHANGE	DATE
A0	INITIAL RELEASE	2012-05-04



- NOTES:
- ELECTRICAL PROPERTIES:
    - 100% open and short test.
    - Conductor resistance: 5 OHMS
    - Insulation resistance: 10 MEGOHMS
    - Hi pot: DC300V/0.01S
    - Audio & Video test, Output resolution: 1920\*1080P
  - All material be ROHS compliant.

9	tag	AV-18C00151	Black background, White character(DP-1030)	1 Pcs
8	Dust cap	OR-0008	DP Dust cap	2 Pcs
7	ferrite core	OR-0016	ferrite core:14.2*28.5*9.5mm	2 Pcs
6	PVC	PVC-0001	60P PVC Black	36.0g
5	copper foil	AV-1TB0012	copper foil:W:35*1.55mm*0.06mm	2 Pcs
4	masking tape	AM-1JZ0006	masking tape:W=30mm	100mm
3	PE	PE-0001	LDPE (RoHS)	22.0g
2	Connector	CN-C0012	DP(R/D),Gold-plated	2 Pcs
1	Cable	DP1-60-3034	(7/0.10TX)P+D+AL+MYLAR(X)SP+7/0.10TX)S+C+F+A+DBI(6/5/0.12(A)MA) JACKET PVC BLACK, OD:6.0±0.20mm L=2960±15/40mm	1 Pcs
NO.	Material name	Item number	Specifications Description	Quantity

图号 (DWG NO)	XY-A0162	#数 (UNIT):	MM						
版次 (REV):	A0	比例 (SCALE)	1:1						
设计 (DESIGN)	Dean	审核 (CHECKED)		核准 (APPROVED)					
品名 (ITEM NO)		料号 (PART NO)							



品名(ITEM NO)  
料号(PART NO)  
DP-1030